

Toner Cable TGT Series 12 Port 1 GHz Taps

Model# TGT12-*

Return Loss		5-15 MHz	15-40 MHz	40-550 MHz	550-1000 MHz
	Input	≥23 dB	≥25 dB	≥20 dB	≥20 dB
	Output	≥25 dB	≥25 dB	≥22 dB	≥20 dB
	Tap	≥25 dB	≥28 dB	≥20 dB	≥20 dB

Isolation		5-15 MHz	15-40 MHz	40-550 MHz	550-1000 MHz
	Port to Port	≥32 dB	≥35 dB	≥27 dB	≥27 dB
	Tap to Output	≥40 dB	≥40 dB	≥27 dB	≥26 dB

Model	Tap Value –1.0 dB	Maximum Insertion Loss (dB) at frequency			
		5-15 MHz	15-40 MHz	40-550 MHz	550-1000 MHz
12 PORT (– 2 dB)					
TGT12-17	17.5 dB	2.6	2.6	3.0	3.5
TGT12-20	20.0 dB	2.0	2.0	2.3	2.5
TGT12-23	22.5 dB	1.4	1.4	1.7	2.3
TGT12-26	26.0 dB	1.0	1.0	1.3	1.6
TGT12-29	29.0 dB	0.7	0.7	0.9	1.5